



Max Working Pressure (bar)			Nominal Size		Dimensions							Bolts	
Part No	Bolts 8.8 (ML)	Bolts 10.9 (MH)	ISO [DN]	SAE (inch)	BLIND MONO FLANGE	D	F	G	H	I	Z	metric	UNC
Standard Pressure Series (according to ISO6162-1) 3000 PSI Series													
384	350	350	13	1/2"	FMB-3---1/2"	16	47	57	17,5	38,1	8.8	M 8x30	5/16"-18x1"1/4
385	350	350	19	3/4"	FMB-3---3/4"	18	50	67	22,3	47,6	10.5	M 10x35	3/8"-16x1"1/2
386	250	315	25	1"	FMB-3---1"	19	54	72	26,2	52,4	10.5	M 10x35	3/8"-16x1"1/2
387	200	250	32	1"1/4	FMB-3---1"-1/4"	18	66	82	30,2	58,7	10.5	M 10x40	7/16"-14x1"1/2
388	200	200	38	1"1/2	FMB-3---1"-1/2"	20	79	96	35,7	69,9	13.5	M 12x45	1/2"-13x1"3/4
389	160	200	51	2"	FMB-3---2"	20	88	102	42,9	77,8	13.5	M 12x45	1/2"-13x1"3/4
390	100	160	64	2"1/2	FMB-3---2"-1/2"	20	100	114	50,8	88,9	13.5	M 12x45	1/2"-13x1"3/4
397	100	160	76	3"	FMB-3---3"	24	127	137	61.9	106.4	17	M 16x50	5/8" -11x2"

High Pressure Series (according to ISO 6162-2) 6000 PSI Series													
391	350	400	13	1/2"	FMB-6---1/2"	16	47	57	18,2	40,5	8.8	M 8x30	5/16"-18x1"1/4
392	350	400	19	3/4"	FMB-6---3/4"	19	54	72	23,8	50,8	10.5	M 10x35	3/8"-16x1"1/2
393	350	400	25	1"	FMB-6---1"	24	68	82	27,8	57,2	13	M 12x45	7/16"-14x1"3/4
394	350	400	32	1"1/4	FMB-6---1"-1/4"	27	79	95	31,8	66,6	15	M 14X50	
395	350	400	38	1"1/2	FMB-6---1"-1/2"	30	88	108	36,5	79,3	17	M 16x55	5/8"-11x2"1/4
396	350	400	51	2"	FMB-6---2"	30	115	134	44.5	96.8	21	M20x65	3/4"-10x2"3/4

How to Order	
Description	3000 PSI 1/2" SAE BLIND MONO FLANGE
Material	AISI 316
Plating	Zinc Nickel
Part No	0100-4-Z

Mat.	St52-3	A105	AISI304	AISI316	SAE1040	
Code	-1	-2	-3	-4	-5	

***Blind flange in carbon steel comes with Black Oxidised treatment.

Plating	Trivalent	Hexavalent	Zinc Nickel
Code	-T	-H	-Z