



Max Working Pressure ( bar )			Nominal Size		Dimensions ( mm )										Threads
Part No.	Bolts 8.8	Bolts 10.9	ISO [DN]	SAE	STRAIGHT VERSION, ORING FACE	A	B	D	F	G	H	I	L	M	metric.

### Standard Pressure Series (according to ISO6162-1) 3000 PSI Series

0169	350	350	13	1/2"	IFL SW 1/2"	13	22	16	47	57	17,5	38,1	36	18	M 8
0170	350	350	19	3/4"	IFL-3-SW-3/4"	19	28	18	50	67	22,3	47,6	36	18	M 10
0171	250	315	25	1"	IFL-3-SW-1"	25	35	18	54	72	26,2	52,4	38	18	M 10
0172	200	250	32	1 1/4"	IFL-3-SW-1 1/4"	31	43	21	68	82	30,2	58,7	41	20	M10
0173	200	200	38	1 1/2"	IFL-3-SW-1 1/2"	38	51	25	79	96	35,7	69,9	44	22	M12
0174	160	200	51	2"	IFL-3-SW-2"	47	61	25,5	88	102	42,9	77,8	45	24	M12
0175	100	160	64	2 1/2"	IFL-3-SW-2 1/2"	63	73	26	101	115	50,8	88,9	50	28	M12
0176	100	100	76	3"	IFL-3-SW-3"	70	90	27,5	124	137	61,9	106,4	50	28	M 16

### High Pressure Series (according to ISO 6162-2) 6000 PSI Series

0177	350	400	13	1/2"	IFL 6 SW 1/2"	13	22	16,5	47	57	18,2	40,5	36	19	M 8
0178	350	400	19	3/4"	IFL-6-SW-3/4"	18	28	20	54	72	23,8	50,8	36	20	M 10
0179	350	400	25	1"	IFL-6-SW-1"	22	35	24	68	82	27,8	57,2	44	22	M 10
0180	350	400	32	1 1/4"	IFL-6-SW-1 1/4"	32	42,8	27,5	79	95	31,8	66,6	44	22	M12
0181	350	400	38	1 1/2"	IFL-6-SW-1 1/2"	38	48,6	31	88	108	36,5	79,3	51	24	M16
0182	350	400	51	2"	IFL-6-SW-2"	51	61	37	118	137	44,5	96,8	70	33	M20

### How to Order

Description	3000 PSI 1/2" INTEGRATED FEMALE THREADED WITH FLAT FACE.
Material	AISI 316
Plating	Zinc Nickel
Part No	<b>0169-4-Z</b>

Mat.	St52-3	A105	AISI304	AISI316	SAE1018	
Code	-1	-2	-3	-4	-6	

\*\*\*Unless Specified Parts will be Black Oxidised.

Plating	Trivalent	Hexavalent	Zinc Nickel
Code	-T	-H	-Z